

SAFETY DATA SHEET

Revision Date 15-May-2020 Version 4

1. IDENTIFICATION

Product identifier

Product Name ULTRA SYNTHETIC RTV GASKET MAKER 3.5 OZ

Other means of identification

Product Code 82135

Recommended use of the chemical and restrictions on use

Recommended Use Sealant

Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address

ITW Permatex 6875 Parkland Blvd. Solon, Ohio 44139 USA Telephone: 1-87-Permatex

(866) 732-9502

24-hour emergency phone number

Chem-Tel: 800-255-3924 International Emergency: 00+1+ 813-248-0585

Contract Number: MIS0003453

E-mail address: mail@permatex.com

May Also Be Distributed by:

ITW Permatex Canada 101-2360 Bristol Circle

Oakville, ON Canada L6H 6M5 Telephone: (800) 924-6994

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin sensitization	Category 1
Carcinogenicity	Category 2

Label elements

Emergency Overview

Signal word Warning

May cause an allergic skin reaction Suspected of causing cancer

Revision Date 15-May-2020



Appearance Black Physical state Paste Liquid Odor Mild

Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Avoid breathing dust/fume/gas/mist/vapors/spray

Contaminated work clothing should not be allowed out of the workplace

Wear protective gloves

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Specific treatment (see .? on this label)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eve irritation persists: Get medical advice/attention IF ON SKIN: Wash with plenty of soap and water

If skin irritation or rash occurs: Get medical advice/attention

Wash contaminated clothing before reuse

Precautionary Statements - Storage

Store in a well-ventilated place Keep container tightly closed

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

Not applicable.

Unknown acute toxicity 0% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
CALCIUM CARBONATE	471-34-1	15 - 40
LIMESTONE	1317-65-3	10 - 30
CARBON BLACK	1333-86-4	1 - 5
2-BUTANONE OXIME	96-29-7	0.1 - 1

4. FIRST AID MEASURES

Description of first aid measures

General advice If symptoms persist, call a physician.

82135 - ULTRA SYNTHETIC RTV GASKET MAKER 3.5 OZ

.5 02

Eye contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms

Revision Date 15-May-2020

persist, call a physician.

Skin contact IF ON SKIN: Wash skin with soap and water. If skin irritation or rash occurs: Get medical

advice/attention. Wash contaminated clothing before reuse. Immediate medical attention is not required. Wash off immediately with soap and plenty of water while removing all

contaminated clothes and shoes. If skin irritation persists, call a physician.

Inhalation Immediate medical attention is not required. If symptoms persist, call a physician. Move to

fresh air in case of accidental inhalation of vapors or decomposition products.

Ingestion Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth

to an unconscious person. Call a physician. Do NOT induce vomiting.

Self-protection of the first aiderUse personal protective equipment as required.

Most important symptoms and effects, both acute and delayed

Symptoms See section 2 for more information.

Indication of any immediate medical attention and special treatment needed

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Use, Use dry chemical, Carbon dioxide (CO2), Water spray (fog), Alcohol resistant foam

Unsuitable extinguishing media

None

Specific hazards arising from the chemical

Keep product and empty container away from heat and sources of ignition. Risk of ignition.

Explosion data

Sensitivity to Mechanical Impact None.
Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

personnel to safe areas. Keep people away from and upwind of spill/leak. Pay attention to

flashback. Take precautionary measures against static discharges.

Environmental precautions

Environmental precautions See section 12 for additional ecological information. Do not flush into surface water or

sanitary sewer system. Prevent further leakage or spillage if safe to do so. Prevent product

from entering drains.

Methods and material for containment and cleaning up

Revision Date 15-May-2020 3.5 OZ

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Ensure adequate ventilation. Flood with water to complete polymerization and scrape off

floor. Sweep up and shovel into suitable containers for disposal. Slipperv. can cause falls if walked on. Soak up with inert absorbent material. Dam up. Pick up and transfer to properly

labeled containers. Take precautionary measures against static discharges.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Use with local exhaust ventilation. All equipment used when handling the product must be Advice on safe handling

grounded. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use

personal protective equipment as required. Do not breathe

dust/fume/gas/mist/vapors/spray. Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapors).

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from

> moisture. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep containers tightly closed in a cool, well-ventilated

place. Keep away from heat. Keep in properly labeled containers.

Incompatible materials Strong oxidizing agents, Acids, Water

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
CALCIUM CARBONATE	-	-	TWA: 10 mg/m ³ total dust
471-34-1			TWA: 5 mg/m ³ respirable dust
LIMESTONE	-	TWA: 15 mg/m³ total dust	TWA: 10 mg/m ³ total dust
1317-65-3		TWA: 5 mg/m³ respirable fraction	TWA: 5 mg/m ³ respirable dust
		(vacated) TWA: 15 mg/m³ total	
		dust	
		(vacated) TWA: 5 mg/m³ respirable	
		fraction	
CARBON BLACK	TWA: 3 mg/m ³ inhalable particulate	TWA: 3.5 mg/m ³	IDLH: 1750 mg/m ³
1333-86-4	matter	(vacated) TWA: 3.5 mg/m ³	TWA: 3.5 mg/m ³
			TWA: 0.1 mg/m³ Carbon black in
			presence of Polycyclic aromatic
			hydrocarbons PAH

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers

Evewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Tight sealing safety goggles. Eye/face protection

3.5 OZ

Revision Date 15-May-2020

Skin and body protection Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.

Respiratory protectionUse NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as

appropriate.

General Hygiene Considerations When using do not eat, drink or smoke. Regular cleaning of equipment, work area and

clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state Paste Liquid
Appearance Black
Odor Mild

Odor threshold No information available

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

pH No information available

Melting point / freezing pointNo information availableBoiling point / boiling rangeNo information availableNotPolymerization

Applicable

Flash point > 93 °C / > 199 °F Tag Closed Cup

Evaporation rate
No information available
No information available
No information available

Flammability Limit in Air

Upper flammability limit:No information availableLower flammability limit:No information available

Vapor pressure <5 mm Hg @ 80°F

Vapor density >1 Air = 1

Relative density 1.44

Water solubility Not applicable

No information available Solubility(ies) **Partition coefficient** No information available **Autoignition temperature** No information available No information available **Decomposition temperature** Kinematic viscosity No information available No information available **Dynamic viscosity Explosive properties** No information available **Oxidizing properties** No information available

Other Information

Softening point

Molecular weight

No information available
No information available

VOC Content (%) <3%

Density

Bulk density

SADT (self-accelerating

No information available
No information available
No information available

decomposition temperature)

10. STABILITY AND REACTIVITY

Polymerization

Reactivity

No information available

Chemical stability

Stable under normal conditions

Possibility of Hazardous Reactions

None under normal processing.

5.5 02

Revision Date 15-May-2020

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Strong oxidizing agents, Acids, Water

Hazardous Decomposition Products

Carbon oxides

Nitrogen oxides (NOx)

Formaldehyde

May release 2-butanone oxime (ethyl methyl ketoxime) at elevated temperature

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation May cause irritation of respiratory tract.

Eye contact Contact with eyes may cause irritation. May cause redness and tearing of the eyes.

Skin contact May cause skin irritation and/or dermatitis. May cause sensitization by skin contact.

Ingestion Ingestion may cause irritation to mucous membranes.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
CALCIUM CARBONATE	= 6450 mg/kg (Rat)	-	-
471-34-1			
CARBON BLACK	> 15400 mg/kg (Rat)	> 3 g/kg (Rabbit)	-
1333-86-4			
2-BUTANONE OXIME	= 930 mg/kg (Rat)	1000 - 1800 mg/kg (Rabbit)	> 4.83 mg/L (Rat) 4 h
96-29-7			

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

SensitizationNo information available.Germ cell mutagenicityNo information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
CARBON BLACK	A3	Group 2B	-	X
1333-86-4				

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Target Organ Effects Eyes, Respiratory system, Skin, Lymphatic System.

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 16859 mg/kg **ATEmix (dermal)** 30196 mg/kg

12. ECOLOGICAL INFORMATION

Ecotoxicity

0 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

82135 - ULTRA SYNTHETIC RTV GASKET MAKER

3.5 OZ

Revision Date 15-May-2020

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility

No information available.

Chemical Name	Partition coefficient
2-BUTANONE OXIME	0.65
96-29-7	

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Do not reuse container.

US EPA Waste Number Not applicable

14. TRANSPORT INFORMATION

DOT

Ethanol Not regulated

IATA

Ethanol Not regulated

IMDG

Ethanol Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA Complies Complies **DSL/NDSL** Not determined **EINECS/ELINCS** Not determined **ENCS IECSC** Complies Complies **KECL PICCS** Complies **AICS** Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances **IECSC** - China Inventory of Existing Chemical Substances

Revision Date 15-May-2020

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

Acute health hazard Yes
Chronic Health Hazard No
Fire hazard Yes
Sudden release of pressure hazard No
Reactive Hazard No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemic	al Name	California Proposition 65
	N BLACK 3-86-4	*Carcinogen (airborne, unbound particles of respirable size)

^{• *}The asterisked chemical(s) listed are not subject to Proposition 65 because they are not airborne in the finished product **U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania
LIMESTONE	X	X	X
1317-65-3			
CARBON BLACK	X	X	X
1333-86-4			

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

WHMIS Hazard Class

D2B - Toxic materials

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA Health hazards 2 Flammability 2 Instability 0

HMIS Health hazards 2 Flammability 2 Physical hazards 0 Personal protection B

NFPA (National Fire Protection Association)
HMIS (Hazardous Material Information System)

Revision Date 15-May-2020

Disclaimer

Illinois Tool Works Inc. believes the information contained in this data sheet is accurate as of the date compiled.

Revision Date 15-May-2020

However, Illinois Tool Works Inc. makes no warranty, express or implied, as to the accuracy, reliability or completeness of the information. User is responsible for evaluating whether such information or this product is fit for a particular purpose and suitable for a particular use or application. The information in this data sheet may not be valid if this product is used in combination with other products or in processes for which it was not designed. Illinois Tool Works Inc. disclaims any liability for consequential or incidental damages of any kind, including lost profits, arising from the sale or use of this product. Ensure you have the most current version of this data sheet by contacting us or reviewing our web site.

End of Safety Data Sheet