



The edges of a sports field are difficult to maintain and are often forgotten. GKB has the perfect solution for this with the Rotobrush. It is important that moss and algae do not get a chance to grow on your field. This causes slipperiness and contamination, which is bad for the playing quality. The edges of the field are extra sensitive to the growth of moss, and together with the fact that this is difficult to reach, makes the Rotobrush an indispensable machine for your sports field. Cleaning the edges of your artificial grass sportfield has never been so easy!



The Rotobrush is available in 2 versions. The RB040 is a single $\varnothing 40$ cm brush on a long arm. Optionally, a $\varnothing 60$ cm brush can be mounted. There is also the option to operate the RB040 hydraulically. In addition to the RB040, an RB120 is also available. This machine has 2 brushes of $\varnothing 60$ cm mounted and is adjusted in such a way that not even a centimeter is skipped.



The Rotobrush is equipped with brushes with extra stiff bristles that penetrate the artificial grass well. In our own contractor, the rotobrush is used on sports fields, but also for the maintenance of various playgrounds. The fact that we also use the Rotobrush ourselves shows that we believe in our own product. Every GKB machine is made as we would like it ourselves, and that is exactly the quality you want.

THE WORKER IS KING



Rotobrush

Specifications:

Type	RB040	RB120
Working width	40 cm / 16"	120 cm / 47"
Working depth	0 - 4 cm / 0 - 1,6"**	0 - 4 cm / 0 - 1,6"**
Maximum dimensions (L x W x H)	60/165 x 90/190 x 80 cm / 24/65 x 36/75 x 32"	90 x 120 x 80 cm / 37 x 47 x 32"
Dimensions during transport (L x W x H)	60/125 x 90/150 x 80 cm / 24/49 x 36/59 x 32"	90 x 120 x 80 cm / 37 x 47 x 32"
Weight	65 kg / 145 lbs	85 kg / 190 lbs
Power requirement	15 - 35 hp	20 - 45 hp
Linkage	Standard three-point hitch cat I - II	Standard three-point hitch cat I - II
Operating speed	0 - 4 km/h / 0 - 2,5 mph**	0 - 4 km/h / 0 - 2,5 mph**
Options		
Brush ø 60 cm	x	-
Central brush ø 60 cm beneath hitch	x	-
Hydraulically adjustable	x	-
Function		
Position	The RB040 and RB120 can be used on both the front and rear of the tractor.	
Comments		
*	The working depth depends entirely on the working speed and the surface.	
**	The working speed depends entirely on the working depth and the surface.	

THE WORKER IS KING