



Are you looking for a way to deal with annual meadow grass, moss, weeds or a greasy top layer? would you like to keep your field in top condition? Then the Vstrong is the perfect machine for you! The Vstrong is a powerful scarifying machine that can be equipped with scarifying blades of different thicknesses and is available in different widths, from 1.20m to 2.40m. The working depth can be easily adjusted by means of the spindles, and the outflow can be lowered if desired by means of the hydraulically operated valve.



At the heart of the Vstrong is the rotor shaft, which can be fitted with the various scarifying blades. By using balancing weights, you can choose a center-to-center distance of 25, 50 or 75mm. The Vstrong is standard equipped with carbide 3mm scarifying blades. In combination with a counter-rotating direction, the Vstrong does not skip an inch.



The VS120 and VS160 are optionally also available with a collection container. This allows you to work very cleanly if desired, which is very desirable on the greens, for example. The collection containers are 200-265 liters and can be tipped hydraulically. This keeps your greens or sports field clean, so you don't have to go over the field twice. This makes the Vstrong the ideal machine for your golf course or sports field!

**THE WORKER IS KING**



## Vstrong Specifications:

Type	VS120	VS160	VS200	VS240
Working width	120 cm / 48"	160 cm / 63"	200 cm / 79"	240 cm / 95"
Working depth	0 - 5 cm / 0 - 2"*	0 - 5 cm / 0 - 2"*	0 - 5 cm / 0 - 2"*	0 - 5 cm / 0 - 2"*
Dimensions (L x W x H)	125 x 165 x 100 cm / 49 x 65 x 39"	135 x 200 x 110 cm 53 x 79 x 43"	155 x 245 x 110 cm / 61 x 97 x 43"	155 x 280 x 110 cm / 61 x 110 x 43"
Dimensions incl. collection bin (L x W x H)	135 x 165 x 100 cm / 53 x 65 x 43"	145 x 200 x 110 cm / 57 x 79 x 43"	-	-
Capacity container	200 l	265 l	-	-
Weight	350 kg / 1060 lbs	500 kg / 1100 lbs	750 kg / 1655 lbs	900 kg / 1985 lbs
Power requirement	35 - 45 hp + creeper gear	40 - 70 hp + creeper gear	65 - 95 hp + creeper gear	90 - 110 hp + creeper gear
Pump capacity oil	20 l/min	30 l/min	40 l/min	50 l/min
Max. hydraulic pressure	150 bar	150 bar	150 bar	150 bar
Linkage	Standard three- point hitch cat I - II	Standard three- point hitch cat I - II	Standard three- point hitch cat I - II	Standard three- point hitch cat I - II
Operating speed	0 - 12 km/h / 0 - 7,5 mph**	0 - 12 km/h / 0 - 7,5 mph**	0 - 12 km/h / 0 - 7,5 mph**	0 - 12 km/h / 0 - 7,5 mph**
<b>Options</b>				
Vertiblade 2 mm	22/44	30/60	38/76	46/92
Vertiblade 3 mm	22/44	30/60	38/76	46/92
Vertiblade 4 mm	22/44	30/60	38/76	46/92
<b>Comments</b>				
*	The working depth depends entirely on the working method, working depth and surface.			
**	The working speed depends entirely on the working method, working depth and surface.			

**THE WORKER IS KING**