



GKB Topdrop



Do you want to provide your sports field or golf course with exactly the right amount of sand? Do you want to easily apply the infill material when laying an artificial turf pitch? Or do you have other material that you want to spread accurately? The Topdrop enables the precise application of various materials. The fact that GKB itself is also a contractor can be seen in the build quality of the Topdrop. Our machines are designed and manufactured as we would like them ourselves. This makes the Topdrop the best brush dresser for your field!



The material is transported to the metering valve by means of a conveyor belt. It is then spread behind the machine by the brush. Both the speed of the conveyor belt, the opening of the dosing valve and the position and speed of the brush can be adjusted, so that you can adjust the Topdrop exactly as you want it. This allows you to apply the material exactly in the right way and in the right place.



The Topdrop is equipped with four balloon tires for optimum ground pressure. The TD330 can optionally be equipped with a bumper with lighting and an overrun brake for use on public roads. The Topdrop is available in four different versions with different working widths and sand bunker capacity. This variation ensures that there is always a Topdrop that suits you!

THE WORKER IS KING



Topdrop Specifications:

Type	TD114	TD214	TD220	TD330
Working width	140 cm / 55"	140 cm / 55"	200 cm / 79"	200 cm / 79"
Dimensions (L x W x H)	300 x 170 x 160 cm / 118 x 67 x 63"	400 x 170 x 160 cm / 158 x 67 x 63"	300 x 230 x 170 cm / 118 x 91 x 67"	400 x 230 x 160 cm / 158 x 91 x 63"
Capacity sandbunker	1,0 m ³ / 36 ft ³	2,0 m ³ / 71 ft ³	2,0 m ³ / 71 ft ³	3,3 m ³ / 117 ft ³
Weight	775 kg / 1710 lbs	1100 kg / 2425 lbs	1200 kg / 2645 lbs	1500 kg / 3310 lbs
Power requirement	20 - 40 hp	30 - 50 hp	30 - 50 hp	45 - 65 hp
Pump capacity oil	25 l/min	25 l/min	25 l/min	25 l/min
Max. hydraulic pressure	150 bar	150 bar	150 bar	150 bar
Linkage	Drawbar eye	Drawbar eye	Drawbar eye	Drawbar eye
Operating speed	0 - 8 km/h / 0 - 5 mph*	0 - 8 km/h / 0 - 5 mph*	0 - 8 km/h / 0 - 5 mph*	0 - 8 km/h / 0 - 5 mph*
Options				
Bumper, lighting and brake for public road use (167/2013/EC)	-	-	-	x
Comments				
	* The working speed depends entirely on the spreading material and desired spreading thickness.			

THE WORKER IS KING