



GKB Sandspreader



Do you strive to keep your golf course or sports field in top condition? The GKB Sandspreader is the right machine to distribute a wide variety of materials evenly over your field. This way you can sand your grass on the golf course or sports field, both during construction and during maintenance. The Sandspreader is equipped with 4 balloon tires to distribute the pressure on the ground as well as possible, preventing damage. This ensures that the Sandspreader is the perfect sander for your golf course or sports field!



The SP100 comes in two versions. In addition to being available with a wheelset, it is also available as a superstructure for a Progator, Workman or Truckster. The SP100 is the largest mounted sand spreader on the market, with a flat-filled bunker capacity of $1\text{m}^3/36\text{ft}^3$. The SP100 is built with a strong bunker and with the optional hydraulic control, this is the perfect machine for your sports field or golf course.



The SP230, SP300 and SP400 are GKB's larger sand spreaders, with a capacity of 2.3m^3 , 3m^3 and 4m^3 . These are also available in an SPM variant. The SPM is a Sandspreader with a sand slide at both the front and the rear. At the front is a hydraulically operated elevator belt. This makes the SPM the ideal machine to refill machines such as the GKB Drainmaster. The SPM is also very suitable for filling sand bunkers and trenches.

THE WORKER IS KING



Sandspreader

Specifications:

Type	SP100 / superstructure	SP230 / SPM230	SP300 / SPM300	SP400 / SPM400
Working width	2 - 12 m / 6,5 - 39 ft	2 - 12 m / 6,5 - 39 ft	2 - 12 m / 6,5 - 39 ft	2 - 12 m / 6,5 - 39 ft
Dimensions SP (L x W x H)	320 x 150 x 140 cm / 126 x 59 x 55"	440 x 190 x 160 cm / 173 x 75 x 63"	515 x 190 x 185 cm / 203 x 75 x 73"	520 x 235 x 205 cm / 205 x 93 x 81"
Dimensions mounted / SPM unfolded (L x W x H)	235 x 150 x 130 cm / 93 x 59 x 51"	470 x 405 x 190 cm / 185 x 160 x 75"	540 x 460 x 190 cm / 213 x 181 x 75"	540 x 500 x 205 cm / 312 x 197 x 81"
Dimensions during transport (L x W x H)	-	470 x 205 x 190 cm / 185 x 81 x 75"	540 x 210 x 190 cm / 213 x 83 x 75"	540 x 235 x 205 cm / 312 x 93 x 81"
Capacity sandbunker	1,0 m ³ / 36 ft ³	2,3 m ³ / 82 ft ³	3,0 m ³ / 106 ft ³	4,0 m ³ / 142 ft ³
Weight	700 / 450 kg / 1540 / 990 lbs	1080 / 1180 kg / 2380 / 2600 lbs	1480 / 1580 kg / 3260 / 3485 lbs	1520 / 1620 kg / 3350 / 3570 lbs
Power requirement	20 - 40 hp	30 - 50 hp	40 - 60 hp	60 - 80 hp
Pump capacity oil	30 l/min	40 l/min	50 l/min	50 l/min
Max. hydraulic pressure	150 bar	150 bar	150 bar	150 bar
Linkage	Drawbar eye	Drawbar eye	Drawbar eye	Drawbar eye
Operating speed	0 - 8 km/h / 0 - 5 mph*	0 - 8 km/h / 0 - 5 mph*	0 - 8 km/h / 0 - 5 mph*	0 - 8 km/h / 0 - 5 mph*

Options

Hydraulic electrical proportional control box	x	x	x	x
Supporting legs, wheelkit and subframe Progator, Workman or Truckster	x	-	-	-
Hydraulically operated sandvalve	x	x	x	x
Rear cross conveyor	x	x	x	x
Bumper, lighting and brake for public road use (167/2013/EC)	-	x	x	x

Option

Bumper, lighting and brake for public road use (167/2013/EC)	Please note that the length, width and weight of the SP230, SP300, SP400, SPM230, SPM300 and SPM400 deviate slightly from the given values when the machine is equipped for use on public roads.
--	--

Comments

* The working speed depends entirely on the desired spread pattern.

THE WORKER IS KING